

Installation: MIXING METHOD

Mixing ratio: 18 - 20 oz of Gravel-Lok liquid : 1 five gallon bucket of stones

Approximate coverage rates for **Gravel-Lok**:

105 sf per five gallon container of Gravel-Lok liquid if troweled out at 2" thick using 18 oz.

90 sf per five gallon container of Gravel-Lok liquid if troweled out at 2" thick using 20 oz.

Roller coat is necessary:

Coverage rate: 400 – 500 square feet per five gallon container.

For driving surfaces please contact Cell-Tek Geosynthetics (888-851-0051) for design advice.

Read MSDS and follow all safety instructions including use of proper eye, skin, and respiratory protection. It is highly recommended you make test samples before starting any job to see the effect of the liquid on the stones. Properly grade subgrade to allow water to flow away from any structures. Add drainage if necessary. Install moisture barrier if project meets a foundation with a basement. Geotextile fabric must separate aggregates from subgrade and soils on all sides of the project. All aggregates must be very clean and free from any fine particles or dirt. The cleaner the stone, the stronger the bond. Store Gravel-Lok at 68 degrees or above until ready to use. Do not install if rain is expected within 12 hours. Do not cover with plastic. This will trap in moisture and cause premature curing. Install when outdoor temperature is 50 degrees or above and will not drop below 50 for at least 12 hours. Allow 24 hours to cure. Rope off treated area to protect it from people and animals.

Excavate Job Site



Install Geotextile Fabric



Install Stabilizer Grid



Infill Grid With 3/4" Washed Aggregates



Spread, Level & Tamp



Install Edge Restraint



Wash Stones And Allow To Dry

Mix Stones With Gravel-Lok In A Cement Mixer Or Wheelbarrow



Pour Out In One Small Area



Level And Trowel To Finish



Allow 24 Hours To Cure



Apply Roller Coat





Providing Architects and Builders with
Superior Paving, Decking and Pedestal Products.

Commercial | Luxury Residential | Municipal

Extended Team

We can also provide technical consultation and installation training for projects that involve Buzon Pedestals. Please contact us to discuss your particular needs. HDG Building Materials also has a network of experienced installers in many major cities. Please contact us for introductions or referrals.

Sales Representatives

Sales representatives for HDG Building Materials are located in the Pacific Northwest, Southern California, and Iowa.

Outside of those regions? No problem, we are happy to serve. Please contact us at 503.360.9551



The logo for CELL-TEK LLC features the words 'CELL-TEK' in a bold, blue, sans-serif font. To the right of 'TEK' is a stylized green leaf-like shape. Below 'CELL-TEK', the letters 'LLC' are written in a smaller, blue, sans-serif font.

HDG Building Materials is an authorized dealer
for Cell-Tek and Gravel-Lok products.
HDG provides architectural sales and support in
North America

HDG Building Materials
Commercial | Luxury Residential | Municipal

10691 SE Jason Lane
Happy Valley, OR 97086

503.360.9551

sales@hdgbuildingmaterials.com